



# MARK 2

+ mid range



By a long way, the  
smallest and lightest  
wearable scanner



Save up to 4 seconds per  
scan



Scan range of  
30–150 cm (12-59 inch)



up to  
6000 scans



3 different wearables to  
choose from

 **868/915  
MHz**

Connection via Bluetooth  
Low Energy and 868/915  
MHz

## MARK 2 mid range



- ✓ Suitable for 1D and 2D barcode reading also from longer distances (30 - 150 cm/12-59 inch)
- ✓ MARK 2 can be connected via Bluetooth Low Energy (BLE) and 868/915 MHz to the end device using the access point
- ✓ Haptic, acoustic and optic feedback function
- ✓ Battery life up to 6000 scans

### USE OF MARK 2 mid range

- ✓ KANBAN (Re-order, Milk Run, etc.)
- ✓ Inbound (Incoming goods, re-distribution)
- ✓ Outbound (palletizing, packaging, outgoing goods, etc.)
- ✓ Transport of Material (high lift stacker, order picking truck)
- ✓ Picking (supermarket principle, small parts picking, etc.)

## ACCESS POINT



- ✓ Transmission via 868/915 MHz, Channel selection is possible
- ✓ Connection via USB or RS232
- ✓ Easy configuration and intergration at: [config.proglove.de](http://config.proglove.de)

## CHARGING STATION



- ✓ Securely holds MARK 2 mid range, standard range and MARK Basic
- ✓ Different mounting types are possible (wall mounting, mounting with cables, etc.)

## MARK 2 mid range



Please contact us for more information:

✉ [info@kfi.it](mailto:info@kfi.it)  
🌐 [www.kfi.it](http://www.kfi.it)

